

IN THE CLAIMS:

1. (currently amended) Golf shoes comprising:

outsoles including multiple jointing holes installing spikes respectively;

uppers sewed or adhered with the outer circumstance of the top of the outsoles; and

mid-soles and insoles stacked sequentially to the outsoles within the uppers, wherein:

protrusions ~~12~~ and ~~12'~~ are protruded from the surroundings of the jointing holes ~~11~~ and ~~11'~~ formed at the outsoles ~~10~~ and ~~10'~~ of the golf shoes, and protruded more and more from the inside to the outside direction to have a slope from the outside to the inside direction;

the inside of the toe of the right outsole ~~[[10']]~~ is rounded to make rotation of the right golf shoe smooth at the finish step; and

the outsole ~~[[10]]~~ of the left golf shoe, making a role of a prop at the finish step, is wider than the outsole ~~[[10']]~~ of the right golf shoe to widen the contact area with the ground in maximum.

2. (currently amended) The golf shoes according to claim 1, wherein:

the rear area of the hard insoles ~~30~~ and ~~30'~~ of the golf shoes includes the impact absorption holes ~~33~~ and ~~33'~~ including the impact absorption plates ~~34~~ and ~~34'~~ to absorb the weight of a golfer and a shock at the impact step; and

F-7938

the insoles ~~30 and 30'~~ are thicker more and more from the outside to the inside direction to make the foot horizontal with the ground when the golfer wears the golf shoes.